

Model	Min. przekrój przewodów przy 30°C(*)	Min. przekrój przewodów przy 45°C(*)	Bezpiecznik (zwłoka D)
<b>Seria BLADE 500</b>			
<b>BLADE 4-5</b>	2,5 mm <sup>2</sup>		16 A
<b>BLADE 7</b>	4 mm <sup>2</sup>	6 mm <sup>2</sup>	25 A
<b>BLADE 11</b>			32 A
<b>Seria RVD 500 / RVD/500</b>			
<b>RVD 7</b>	4 mm <sup>2</sup>	6 mm <sup>2</sup>	25 A
<b>RVD 11</b>			32 A
<b>Seria BLADE 1000 / ERC 1000</b>			
<b>BLADE, ERC 15-18</b>	10 mm <sup>2</sup>	16 mm <sup>2</sup>	50 A
<b>BLADE, ERC 22</b>	16 mm <sup>2</sup>		63 A
<b>Seria ERC 500</b>			
<b>ERC 4-5</b>	2,5 mm <sup>2</sup>	4 mm <sup>2</sup>	16 A
<b>ERC 7</b>	4 mm <sup>2</sup>	6 mm <sup>2</sup>	25 A
<b>ERC 11</b>	6 mm <sup>2</sup>	10 mm <sup>2</sup>	32 A
<b>Seria AC 2000</b>			
<b>ERC 30</b>	25 mm <sup>2</sup>	35 mm <sup>2</sup>	80 A
<b>ERC 37</b>	35 mm <sup>2</sup>		100 A
<b>ERC 45</b>	50 mm <sup>2</sup>		125 A
<b>Seria 6000</b>			
<b>AC 110</b>	185 mm <sup>2</sup>	240 mm <sup>2</sup>	320 A
<b>AC 132</b>	240 mm <sup>2</sup>	2 x 120 mm <sup>2</sup>	400 A
<b>Seria OPTIMA</b>			
<b>OPTIMA 30</b>	25 mm <sup>2</sup>	35 mm <sup>2</sup>	100 A
<b>OPTIMA 37</b>	35 mm <sup>2</sup>		125 A
<b>OPTIMA 45</b>	50 mm <sup>2</sup>	50 mm <sup>2</sup>	160 A
<b>OPTIMA 110</b>	185 mm <sup>2</sup>	240 mm <sup>2</sup>	320 A
<b>Seria RVX / RVX// RVX UP</b>			
<b>RVX 55</b>	50 mm <sup>2</sup>	70 mm <sup>2</sup>	160 A
<b>RVX 75</b>	95 mm <sup>2</sup>	120 mm <sup>2</sup>	200 A
<b>RVX 90</b>			250 A
<b>RVX 45 UP</b>	70 mm <sup>2</sup>	95 mm <sup>2</sup>	160 A
<b>RVX 55-75 UP</b>	95 mm <sup>2</sup>	120 mm <sup>2</sup>	200 A
<b>Seria RVD 2000 / RVD/2000</b>			
<b>RVD 30</b>	35 mm <sup>2</sup>		100 A
<b>RVD 37</b>			125 A
<b>RVD 45</b>			160 A
<b>RVD 55</b>	50 mm <sup>2</sup>		160 A